

Lift and Transport truck HTW 50/130 with 12 Volt Hydraulic Unit



The lift- and transport truck has a rugged, torsion-resistant frame structure, steel powdercoated (grey – RAL 7035) with integrated 12 Volt hydraulic unit for vertical adjustment enables easy handling. The vertical adjustment is controlled via an UP / DOWN foot switch and it has an EMERGENCY OFF switch. A maintenance-free drive battery ensures a constant power supply. Moreover, the unit is supplied with a separate electronic rapid charger. 4 steerable solid rubber wheels, 2 of them lockable, 1 enabling locking as regards to the direction, diameter 125 mm with special roller bearings, permanently lubricated and maintenance-free, which ensure an absolutely noiseless movement. The low deadweight permits straightforward shunting and operation of the lift and transport truck. A special valve ensures even lowering at various loads. A stainless steel roller track comprising 5 carrying rollers of corrosion-resistant material and plastic coating has been arranged on top of the truck. A holding device secures the body tray or coffin plate lying on it. The slide handle of the lift and transport truck can be removed. An anti-collision buffer is mounted to the front end.

Technical Data:

Dimensions lowest Position W/D/H:	2150 x 750 x 320 mm
Dimensions highest Position W/D/H:	2150 x 750 x 1650 mm
Carrying capacity:	max. 250 kg
Dead weight:	approx. 120 kg
Material:	Steel
Colour:	Lightgrey RAL 7035 (powder coated)
Type:	HTW 50/130
Article No.:	050.050.010

Lift and Transport Truck HTW 50/130 – 350 kg

Material: Steel

Article No.: 050.050.090

Additional models see back page

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE - 93049 Regensburg/Germany

Phone +49/941/20 86 48-0
Fax +49/941/20 86 48-29
www.KUGEL-medical.de



Lift and Transport truck HTW 51/130 with 12 Volt Hydraulic Unit – Made of Stainless Steel



The vertical adjustment is controlled via an UP / DOWN foot switch

The lift- and transport truck has a rugged, torsion-resistant frame structure, completely made of stainless steel with integrated 12 Volts hydraulic unit for vertical adjustment enables easy handling. The vertical adjustment is controlled via an UP/DOWN foot switch and it has an EMERGENCY OFF switch. A maintenance-free drive battery ensures a constant power supply. Moreover, the unit is supplied with an separate electronic rapid charger. 4 steerable solid rubber wheels, 2 of them lockable, 1 enabling locking as regards to the direction, diameter 125 mm with special roller bearings, permanently lubricated and maintenance-free, which ensure an absolutely noiseless movement. The low deadweight permits straightforward shunting and operation of the lift and transport truck. A special valve ensures even lowering at various loads. A stainless steel roller track comprising 5 carrying rollers of corrosion-resistant material and plastic coating has been arranged on top of the truck. A holding device secures the body tray or coffin plate lying on it. The slide handle of the lift and transport truck can be removed. An anti-collision buffer is mounted to the front end.

Technical Data:

Dimensions lowest Position W/D/H:	2150 x 750 x 320 mm
Dimensions highest Position W/D/H:	2150 x 750 x 1650 mm
Carrying capacity:	max. 250 kg
Dead weight:	approx. 100 kg
Material:	Stainless steel (Material No. 1.4301 – ANSI 304)
Type:	HTW 51/130
Article No.:	050.120.010

Lift and Transport Truck HTW 51/130 – 350 kg

Material: Stainless Steel Article No.: 050.120.012

KUGEL medical GmbH & Co. KG
Hermann-Köhl-Str. 2A
DE - 93049 Regensburg/Germany

Phone +49/941/20 86 48-0
Fax +49/941/20 86 48-29
www.KUGEL-medical.de

