Lift and Transport Truck HTW 50/140 with Digital Scale





The lift and transport truck has a rugged, torsion-resistant frame structure, steel powder-coated (grey – RAL 7035) with smoothly running, integrated hydraulic unit for foot-actuated vertical adjustment for easy handling. 4 steerable solid rubber wheels, 2 of them lockable, 1 enabling locking as regards to the direction, d = 125 mm with special roller bearings, permanently lubricated and maintenance-free, which ensure an absolutely noiseless movement. A stainless steel roller track comprising 5 carrying rollers of corrosion-resistant material and plastic coating has been arranged on top of the truck. A holding device secures the body tray or coffin plate lying on it. The slide handle of the lift and transport truck can be removed. An anti-collision buffer is mounted to the front end. The low deadweight permits straightforward shunting and operation of the lift and transport truck. A special valve ensures even lowering at various loads. Ready for use digital scale with single-button operation for easy handling. Tarring over the entire weighing range. Easy-to-read LCD display. Operation via 9 Volt block battery includes electronic rapid charger. Easy-care plastic housing, mounted on a stainless steel shelf.

Technical Data:

Dimensions lowest Position W/D/H: $2150 \times 750 \times 360 \text{ mm}$ Dimensions highest Position W/D/H: $2150 \times 750 \times 1710 \text{ mm}$

Carrying capacity: max. 250 kg
Dead weight: approx. 100 kg
Weighting range: 0-200 kg
Precision: +/- 500 g
Material: Steel

Colour: Lightgrey RAL 7035 (powder coated)

Type: HTW 50/140
Article No.: 050.060.010

Additional models see back page

KUGEL medical GmbH & Co. KG Hermann-Köhl-Str. 2A

DE - 93049 Regensburg/Germany

Phone +49/941/20 86 48-0 Fax +49/941/20 86 48-29 www.KUGEL-medical.de





Lift and Transport Truck HTW 51/140 with Digital Scale – Made of Stainless Steel

The lift- and transport truck has a rugged, torsion-resistant frame structure, completely made of stainless steel (Material no. 1.4301 – ANSI 304) with smoothly running, integrated hydraulic unit for foot-actuated vertical adjustment for easy handling. 4 steerable solid rubber wheels, 2 of them lockable, 1 enabling locking as regards to the direction, d = 125 mm with special roller bearings, permanently lubricated and maintenance-free, which ensure an absolutely noiseless movement. A stainless steel roller track comprising 5 carrying rollers of corrosion-resistant material and plastic coating has been arranged on top of the truck. A holding device secures the body tray or coffin plate lying on it. The slide handle of the lift and transport truck can be removed. An anti-collision buffer is mounted to the front end. Ready for use digital scale with single-button operation for easy handling. Tarring over the entire weighing range. Easy-to-read LCD display. Operation via 9 Volt block battery includes electronic rapid charger. Easy-care plastic housing, mounted on a stainless steel shelf.

Technical Data:

Dimensions lowest Position W/D/H: 2150 x 750 x 360 mm Dimensions highest Position W/D/H: 2150 x 750 x 1710 mm

Carrying capacity: max. 250 kg
Dead weight: ca. 100 kg
Weighting range: 0 - 200 kg
Precision: +/- 500 g

Material: Stainless steel (Material No. 1.4301 – ANSI 304)

Type: HTW 51/140
Article No.: 050.130.010



